



SUNPOWER TECHNOLOGY CORP.
 16F-1, No.150, Jian 1st Rd., Zhonghe Dist., New Taipei City 235, Taiwan (R.O.C.).
 TEL: 886-2-8226-3100 FAX: 886-2-8226-3111
 http://www.sunpower.com.tw
 E-mail: sunpower@sunpower.com.tw

SDX-375-G24

**375W, Six Output
 DC-DC for ATX System**



150 x 140 x 86 mm
 5.90 x 5.51 x 3.39 inch



Features:

- * Input and output isolation
- * High efficiency and reliability
- * Soft start function, low inrush current
- * Input reverse polarity protection
- * 3.3V & 5V VRM design
- * Over voltage, over load & short circuit protection
- * With power good signal & PS-ON signal output
- * 100% full load burn-in test
- * Meet Intel ATX 2.31
- * UL, cUL, CB, CE standard
- * 3 years warranty

Specification:

INPUT	Voltage	19V ~ 36V DC (Typical 24V)						
	Current	<20A @ 23V DC input,						
	Protection	Ceramic Fuse 30A/250V						
OUTPUT	Voltage	5V	3.3V	12V1	12V2	-5V	-12V	5Vsb
	Min Load	0A	0A	0.5A	0A	0A	0A	0A
	Max Load	20A	20A	16A	16A	0.5A	1A	2.5A
	Output Tolerance ②	±3%	±5%	±3%	±3%	±5%	±10%	±5%
	Ripple Noise MAX. ③	70mV	70mV	150mV	150mV	100mV	150mV	70mV
	Efficiency (TYP.)	83%						
OUTPUT	Output MAX.	Input Voltage : 19V ~ 23V total output max 300W ; Input Voltage : 23V ~ 36V total output max 375W 3.3V & 5V max 115W, -5V & -12V max 12W						
PROTECTION	Over Voltage	5.7V~6.5V	3.7V~4.1V	13.1V~14.5V		----	----	----
		Shutdown, it needs re-power on to recover						
	Over current (MAX)	25A	25A	20A	20A	----	----	----
PROTECTION	Over Load & Short Circuit	When power supply over 105%~ 150% max load or short circuit acted, power supply will be shutdown and latch off, recover after re-start up.						
ELEC. CHAR.	Rise time	<20mS						
	Power good signal	Power ON within 100---500ms, high level TTL Signal release.						
ENVIRONMENT	Temperature ④	Operating: -20 ~ 70°C ; De-rating: 45 ~ 70°C : 2.5%/°C ; Storage: -40~+85°C						
	Humidity	Operating: 20% ~ 90% (non condensing) RH; Storage: 10% ~ 95% RH (non condensing)						
SAFETY	Withstand voltage	I/P-O/P:3.0KVAC, I/P-FG:1.5KVAC, 1minute						
	Isolation resistance	I/P-O/P, I/P-FG, > 100MΩ/500VDC at 25°C/ 70% RH						
EMC	EMI	EN 55032 CLASS B · FCC CFR 47 PART 15 CLASS B · CNS 13438 CLASS B.						
	EMS	EN 55024 : EN 61000-4-2,3,4,5,6,8						
OTHERS	Cooling	Forced airflow cooling with DC fan						
	M.T.B.F.	215 K hours (min)						
	Dimension	150 x 140 x 86 mm (L*W*H)						
	Packing	N.W.: Kg / 1pc; 6 pcs/ 2.03 CUFT / 1 CTN						


NOTE	①	All measurements which not mentioned are based on 24VDC input, output Max at ambient 25°C / 70%RH.
	②	Output tolerance included set up voltage, line regulation and load regulation. The regulation is measured between 20%-100% max load of each output, Total output t must under output Max .
	③	Ripple & noise are measured at 10~50°C condition and 20MHz of bandwidth by using a 10" ~ 15" twisted pair-wire terminated with a 0.1uF & a 10uF parallel capacitor.
	④	The operating temperature shall follow the de-rating curve in spec
	⑤	The power supply is considered a component of end-equipment. The end-equipment must be re-confirmed whether comply with EMC directives.




SUNPOWER TECHNOLOGY CORP.
 16F-1, No.150, Jian 1st Rd., Zhonghe Dist., New Taipei City 235, Taiwan (R.O.C.).
 TEL: 886-2-8226-3100 FAX: 886-2-8226-3111
 http://www.sunpower.com.tw
 E-mail: sunpower@sunpower.com.tw

SDX-375-G24

De-rating Curve : E2



Output De-rating Vs Input Voltage : DD15



Dimension:

(Unit: mm)

